CONTROL AND SAFETY THERMOSTATS

WTC

Compact contact thermostat with spring for mounting on pipes up to 2". Adjustment range: 30 to 90°C. Differential at 20°C < 10 K. Contact rating: 16 (4) A/230 V. Spring: L= 230 mm.
Compliant with: LVD 2014/35/EU - EMC 2014/30/EU.



Part number	Power supply	IP rating	Q.ty/Box	Box/ Carton
P04075	230V	IP40	1	87

Dimensions on page 61

TRC100


Capillary control thermostat with 2 switching contacts. Copper capillary tube L= 900 mm (bulb 100 mm x Ø 6). Adjustment range: 30 to 90°C. Contact rating 16 (5) A-230 V.
Complete with knob.
Compliant with: LVD 2014/35/EU - EMC 2014/30/EU.



Part number	Power supply	Temp. control range	Q.ty/Box	Box/ Carton
0408200	230V	30–90°C	100	100

TBC100

Capillary safety thermostat with manual resetting. Set temperature: 97°C±3°C. Copper capillary tube L= 900 mm (bulb 100 mm x Ø 6). Contact rating: 16 (5) A-230 V.
Compliant with: LVD 2014/35/EU - EMC 2014/30/EU.



Part number	Power supply	Contact rating	Q.ty/Box	Box/ Carton
0408500	230V	16 (5) A - 250V	125	125

MTV

Bimetallic contact micro-thermostat for fan coils. Starts the fan at a pre-set temperature only. Faston version complete with 250 mm cables, terminal and spring for mounting on pipes. "Pre-wired" version with wired and IP 55 insulated thermostat, 300 mm connection cables and spring for mounting on pipes. Contact rating 10A (2.5) 250V. Contact opening temperature: 35°C. (Fan stops). Contact closing temperature: 42±3°C.
(Fan starts). The 0408303 Series is supplied with cables with 6.3mm F Faston connection on the terminal.
Compliant with: LVD 2014/35/EU - EMC 2014/30/EU.





Part number	Power supply	Connection	Q.ty/Box	Box/ Carton	€/unit
0408301	230V	Faston	25	25	
0408303	230V	Pre-wired	25	25	

CH30

Contact thermostat for max.1/2" pipes. Suitable for automatic Summer/Winter switching for fan coil control. Operating range: 16 ±3.3°C - 26 ± 3.3°C.
T water <16°C: Red-Brown NC➔Summer; T water >26°C: Red-Black NC➔ Winter.
Contact rating 5A-230V switching. Complete with 3x1mm2 cable L=0.3m.



Part number	Contact rating	Cable	Q.ty/Box	Box/ Carton
CH30/1626L2	5A - 230V	0.3m	1	1